

Amendments to the Specification

Please amend the Detailed Description of the Invention as follows:

This invention relates to equal response axles for vehicles 10 having a front engine 15 and a rear wheel drive (non-independent suspension) and is particularly suited for use on racing cars. The invention involves a method and design for equalizing the torque at the tire contact patch. [[The]] As shown in FIG. 3, the engine 15 is connected through a transmission 16 to a drive shaft 17 which drive drives the axels rear axles 13 and 14. In racecars, the right rear axle 13 is normally slightly longer than the left rear axle 14 and this creates problems particularly on turns.

Accordingly, the right and left axles 13 and 14 respectively are machined to different dimensions based on a formula for calculating spring rates (~~tortional~~ torsional stiffness) of torsion bars. “Spring rate” is defined in the ratio as the amount of force required to move a torsion arm one inch. The intention is to have the same spring rates on each axle 13 and 14. Basically, the calculation uses the static loaded radius (dimension from center of axle to ground) using either static or dynamic weight on the tire (portion of tire flat on the ground).

FIG 1 depicts a weight W being applied to the torsion arm at a distance ℓ which results in a 1° twist in the torsion bar having an effective length L.

FIG. 2 illustrates a $10\frac{1}{2}$ ” torsion arm which deflects $2\frac{7}{16}$ ” under the load W which can be assumed as 500 pounds. The angle of twist is $11\frac{1}{2}^\circ$ where ℓ equals $10\frac{1}{2}$ ”. The resultant spring rate is 205 inch pounds. While various assumptions have been made to determine the spring rate, variations in the spring rate vary occur without affecting the theory of this invention.

In Step 1, the polar moment of inertia (J) for a tubular bar is calculated as follows:

STEP 1

Solid Bar

$$J = \frac{(\Pi D^4)}{32}$$

Tubular Bar

$$J = \frac{\Pi (D_1^4 - D_2^4)}{32}$$

where J=Polar moment of inertia
D=Diameter of bar

D_1 =outer diameter
 D_2 =inner diameter

STEP 2

In Step 2, reference should be made to FIG. 1 for the various parameters.

$$F = \frac{W \times L}{[L] \ell}$$

where $F=T$

F =force

T =torque

L =working length

ℓ =lever length of torsion arm

W =weight or load

STEP 3

$$\theta = \frac{T \times L}{G \times J}$$

where W =a select weight

F =force in pounds

T =torque in pounds

J =polar moment

G =~~modules~~ modulus of elasticity in shear (PSI)

L =working length

ℓ =lever length of torsion arm

θ =angle of twist in radians

Note:

- (1) For W use 500 pounds for 1 inch or larger bars
- (2) Use 10,750,000 for G with 4140 steel
- (3) Answer will be in radians

STEP 4

Multiply the answer in Step 3 by 57.3=Degrees of twist; used to convert angle of twist in radians to degrees of twist.

Refer to FIG. 2 for an understanding of Step 5

STEP 5

- (a) Draw a line using torsion arm length
- (b) Draw a second line of the same length representing degrees of twist
- (c) Drive the load by the distance (deflection).

STEP 6

Divide the load by the distance to obtain the spring rate

$$\text{Load}=W=500$$

$$\frac{L}{D} = \frac{500}{2 \frac{7}{16}} = \underline{205 \text{ inch pounds}}$$

$$\text{Distance } 2 \frac{7}{16}$$

Using the above formula to dimension the rear axles on high performance or racing cars overcomes the problems associated with an unequal response as torque is delivered unequally to the rear wheels 11 and 12. The problems are caused by the instantaneous weight transfer to the left rear wheel 11 and the fact that the right side axle 13 is longer than the left side 14, yet both conventionally have the same diameter in the effective length of the axle. The fact that the left side axle is shorter with the same diameter means that the left rear wheel 11 will lose traction first under hard acceleration because the shorter axle 14 has a high spring rate (~~tortionally~~ torsionally stiffer), and the longer axle 13 will twist slightly before spinning the wheel 12. If the right and left axles 13 and 14 are machined to different dimensions determined by the foregoing formulas the problems are overcome. This invention uses the static loaded radius (dimension from center of axle to ground) using either straight static or curved dynamic weight on the tire.

If you are going through a left hand corner and the car has a slight under steer, a softer left rear axle 14 can fix this problem. Also, if you going through a right hand corner under power you must be much more careful not to spin out than if it was a left hand corner. There is a torque reaction that takes weight off the right rear wheel 12 and applies it to the left rear wheel 11.

The weight transfer going through a right hand corner is also transferring weight to the left side wheels 11 together. This is loading up the left rear wheel 11 to the point where spinning out becomes all too easy. However, with the proposed "~~kera~~" "Kera" axles, if you choose to replace the left rear axle 14 with a smaller diameter, (softer spring rate in twist), the instantaneous weight transfer can be softened (absorbed) in the twisting action of the axle 14 which will result in more grip on the race track.

Applications particularly suited for the invention occur in oval track racing cars, open wheel cars, road racing cars, off road racing vehicles, high performance street cars, sport utility vehicles, pick-up trucks and commercial trucks and buses on all live axle rear wheel drive passenger cars.

In drag racing, the "~~kera~~" "Kera" sized axle will allow more even distribution of power under acceleration. Axle sizing is an excellent way of tuning the chassis under acceleration. The "kera" sized axle also helps prevent breakage of drive train parts.

The general advantages for all road vehicles include:

- 1) Less wheel spin under acceleration;
- 2) More even application of torque to drive wheels (even wear);
- 3) Less breakage in drive train;

- 4) Better response under starting acceleration;
- 5) Better grip when applying power through corner;
- 6) More even deceleration;
- 7) Better drive wheel tire wear.

Since applicant's invention is that to have two axles with the same spring rates and two different lengths, the axles must have different diameters. The right and left rear axles have fixed lengths. By calculating the spring rate for the right rear axle, which has a known diameter, the diameter of the left rear axle may be calculated using the same spring rate.

While the invention has been explained by a detailed description of certain specific embodiments, it is understood that various modifications and substitutions can be made in any of them within the scope of the appended claims, which are intended also to include equivalents of such embodiments.